

# OCHSE PROFESSIONAL

## Ochse Series

### Professional

The best vacuum cleaners for professional use on central unit sector. High quality, display remote, simplify installation, different level depression and so on...



# OCHSE PROFESSIONAL

Ochse Professional vacuum units are the best vacuum cleaners for professional use on central vacuum unit sector. Their high quality construction is combined with a **performance electronic management of latest generation**, used to simplify installation and use: everything can be managed by the **new touch screen display**.

## INSTALLATION AREA

**Ochse Professional** vacuum units can be used in buildings with the following features:

- Surfaces up to 3000 m<sup>2</sup>
- Suitable for 4 users maximum
- Pipe network according to the number of users
- Supply: 400 V three-phase
- Continuous use
- External air exhaust



## Ochse Professional SELECTION TABLE

MODEL	Recommended Max surface	ARTICLE	Supply V ac	Max. number of users
Ochse Professional 1000	1000 m <sup>2</sup>	161755	400	2
Ochse Professional 2000	2000 m <sup>2</sup>	161756	400	2/3
Ochse Professional 3000	3000 m <sup>2</sup>	161757	400	4

## MAIN FEATURES OF THE PRODUCT



Maintenance computer



IP protection degree



Optional automatic filter cleaning



Isolation class 1



Energy saving vacuum unit



Max number of users: 3



CE marking

## CHARACTERISTICS

### 1 - New touchscreen interface

The Ochse Professional vacuum units of latest generation have a new 5" touchscreen display that makes their use easier.

The touchscreen display is an easy interface for all users:

- For the installer, that can find all set-ups to manage the working of the vacuum unit;
- For the final user, that can check the system conditions in every moment, with real time messages about required maintenance and instructions to execute them.

Thanks to the graphic display, all maintenance operations are supported by images for immediate understanding, supporting the service staff without the need of the instruction manual.

For the installer, the graphic display means an extra value in these circumstances:

- During the first installation, because a special training is not required, but just follow the wizard;
- During the next maintenance operations it is possible to control all the working parameters on the display, in order to find immediately the correct operation.

The display is nothing but the interface of a real computer set up that rules the vacuum unit and optimizes its performances, stating:

- The depression on the system, with the possibility to modify the vacuum power directly from the display
- The level of the dust container
- The filter efficiency
- The need for scheduled maintenance, showing the phone number that the installer has entered during first installation

Additional functions can be managed from the touch screen:

- Set up of vacuum interruption, in case of warning and/or alarm.
- Test function
- Alarms list archive
- Electrical consumptions of the vacuum unit
- Extraordinary maintenance activities list



### Screen examples:



#### Main screen

It is possible to verify if the vacuum unit is On, the central system depression, all the others control screens.




#### Filter control

Filter efficiency, thanks to the colored status bar, easy to understand.



#### Dust bin emptying

Instructions for dust bin emptying: when the vacuum unit advises that the bin must be emptied, an animation sequence shows how to perform the operation, helping even the inexperienced user.



#### Vacuum unit info

Screen with info about the unit, with all working parameters.



# OCHSE PROFESSIONAL

## 2 -Consumption optimization control




The commitment of Sydmay to reduce consumption of its central vacuum units continues with the new Ochse Professional line: compared to the previous models, new blowing motors have been adopted and they have a better energy efficiency class (IE2 class), able to offer the same vacuum power, with lower consumptions.

The electronic motor maintenance, that optimizes performances and prevents any absorption peaks, can process the data that have been transmitted from a temperature sensor installed on the motor, to act promptly on the operating parameters and avoid possible malfunctions. These features grant a greater reliability.




Ochse Professional units **have a continuous control system of vacuum power**, that allows to maintain it constant even with different use conditions (for example an additional user that starts working or a brush change).

**Then it is possible to set up the depression required:** set up is made with the touchscreen display in a quick and easy way.




Ochse Professional units can manage the suction range when you want. You just enter to the factory parameters, for sure you need input the password first.



At the beginning of adjust the parameters, you should have enough ability to control the range. That means you have enough knowledge in the central vacuum system. That is why we lock these menu and need the password to enter. Any wrong parameters may cause the further damage for the central vacuum unit. Just as the above pictures, you can adjust the motor's min suction and max suction that you want.


## 3 - Automatic filter cleaning

All Ochse vacuum units are designed for the installation of the Autocleaner system: a reversed compressed air spray crosses the filter and the dust on the filter surface or between its folds, can drop inside the dustbin. Autocleaner can be programmed on one's choice and this device can be installed after the vacuum unit installation. All Ochse vacuum units have the Autocleaner arrangement, that consist of pneumatic connections, electrical connections and software for maintenance managing, that offers standard or personalized set up.




## 4 - Remote alarms (optional)

With an optional card that allows connection to an Ethernet network, it is possible to check the status of the central vacuum system from any terminal connected to the network: using a special software to install on the PC, all information are available on the touchscreen display.




# OCHSE PROFESSIONAL

## Ochse Professional



## MEASUREMENTS AND TECHNICAL DATA

Ochse Professional line can be installed for professional and semi-professional uses, with a maximum of three users at the same time. The model can be chosen according to the total surface to clean and the number of users required, in order to grant the vacuum power needed.



		Ochse Professional		
Model Article		Ochse 1000	Ochse 2000	Ochse 3000
		161755	161756	161757
Maintenance computer		YES	YES	YES
Vacuum inlet	Ø mm	80	80	80
Air discharge	Ø mm	80	80	80
IP protection degree		20	20	20
Supply	V ac	400	400	400
Frequency	Hz	50/60	50/60	50/60
Motor power	kW	4	4,3	5,5
Absorption	A	8,1	8,8	11,1
Vacuum inlets supply	V dc	12	12	12
Speed electronic converter		YES	YES	YES
Maximum Depression	mbar	325	345	360
Maximum air flow	m³/h	550	560	570
Filtering surface	cm²	17800	17800	17800
Dust bin capacity	L	550	560	570
Air discharge		YES	YES	YES
Air discharge silencer		YES	YES	YES
Weight	kg	145	146	148
Measurements A	mm	750	750	750
Measurements B	mm	633	633	633
Measurements C	mm	1670	1670	1670
Measurements D	mm	827	827	827
Measurements E	mm	642	642	642
Measurements F	mm	750	750	750
Measurements G	mm	600	600	600
Noise	dB(A)	60-80		

**N. B.:** Nominal noise values. Values may vary according to environment and manner in which the unit is installed.

\*these models are supplied with a sleeve 63/80 to connect the vacuum unit to the pipe network.

## CERTIFICATIONS

**CE** CE marking  
IP protection degree

**IP 20**  
Electrical insulation

**CLASS I**

Linea Ochse Professional  
Device in compliance with the following standards:

EC DIRECTIVES  
- 2006/42/CE  
- 2006/95/CE  
- 2004/108/CE

APPLIED HARMONISED STANDARDS  
- EN 60335-1 : 2012  
- EN 60335-2-2 : 2010  
- EN 61000-3-2 : 2006 + A2 : 2009

- EN 61000-3-3 : 2008  
- EN 55014-1 : 2006 + A1 : 2009  
- EN 55014-2 : 1997 + A2 : 2008  
- EN 62233 : 2008

ROHS DIRECTIVE 2002/95  
COMPLIANCE TO REACH DIRECTIVES.

N.B. installation must be carried out in strict compliance with current regulations.

# OCHSE PROFESSIONAL

## TECHNICAL FEATURES

Ochse Professional vacuum units are designed and produced in conformity with all current regulations and European directives, whilst taking into account functionality, power and capacity.

Main technical characteristics can be listed as follows:

- Metal cylindrical frame painted with epoxy powder
- Base coated with anti-shock material to protect the vacuum unit.
- Metal dustbin with wheels (capacity 62/106 litres)
- Bag with bag stretchers inside the dustbin, to dispose of dust quickly and hygienically.
- Possible connection to the piping from the right or from the left side, independently of each other.
- Single-phase and three-phase power supply
- Side-channel motor-pump group with light alloy case, high-performance and maintenance-free; professional motor with CE marking, IP 55 protection degree, F IEC 2 class, with integrated silencer.
- Thermal protector PTO
- Mechanical breaker valve
- Automatic adjustment of vacuum power (inverter)
- Vacuum power customizable set up
- Maintenance computer with touchscreen interface
- Pressure transducer for vacuum performance reading
- Class M polyester filter, water washable.
- **Filter protection for a reduced maintenance.**
- Vacuum inlets supply: 12 V.
- Complete with silencer and sleeves for pipe network connection
- Suitable for all Sydmay cleaning accessories
- Possibility to combine, even after installation, the automatic filter cleaning system Autocleaner (see page ...)

## INSTALLATION FEATURES

Vacuum units are equipped with an air discharge connection, in order to expel dust particles that the filter cannot hold outside. They can be placed in soundproofed technical rooms or utility rooms (for example garages, basements, etc...) to protect the other rooms from noise and to keep them protected from bad weather, humidity and temperature leaps. Keep away from heat sources, such as stoves or radiators. (N.B.: IP protection degree 20).

In the design stage, we recommend identification of the best location for the central unit with respect to the system, leaving a reasonable space for installation, use, maintenance, a proper air exchange around the unit and passive acoustic requirements of the building.

If the system is installed in a building with several floors, we suggest placing the vacuum unit on the bottom floor.

In case of exposed pipes, to avoid the sediment of dusts on the walls close to the pipes caused by static charges, we recommend to make the pipe network with metal pipes, connected to the ground.

## INSTALLING THE CENTRAL UNIT


The vacuum unit does not require special anchoring. However, it is important to check that the area for installation has the following minimum requirements, in order to be correctly and securely positioned.

- a perfectly flat, horizontal and solid surface, without cracks.
- a vibration free surface. Furthermore it is essential that there are no disconnections that could make the central unit instable.

## PIPE CONNECTION


Connections to pipe network and to air expulsion can be made on the left or on the right side of the vacuum unit.

**WARNING:** if the discharge pipe is longer than 5 meters it is necessary to install a bigger diameter in order to reach the optimal conditions for air expulsion.



## EASY BIN EMPTYING

Ochse Professional vacuum units have a dust container with an easy opening system and a soft touch handle coated in shockproof material.



## DUST CONTAINER WITH WHEELS

Thanks to its wheels, the dust container can be moved easily.

